

Earscan 3 Pure Tone Audiometers

Model Comparison

	ES3M	ES3S	ES3
Limited Frequency, 250 to 8000 Hz	✓		
Full Frequency, 125 to 8000 Hz		✓	✓
Hearing Level Range: -10 to 80 db HL	✓	✓	
Hearing Level Range: -10 to 100 db HL			✓
Manual Threshold	✓	✓	✓
Automatic Screening (NOT suitable for OSHA testing)		✓	
Automatic Threshold (Modified Hughson-Westlake)			✓
Talkover (Operator to patient communication)	✓	✓	✓
Binaural Stimulus Presentations	✓	✓	✓
TDH-39 Earphones		✓	✓
DD45 Earphones	✓		
Sound Room Patch Cords			✓
Subject Response Button		✓	✓
Carrying Case	✓	✓	✓
Battery Power (4 AA, included)	✓	✓	✓
A/C Power Adapter or USB Powered	✓	✓	✓
Data Transfer to PC or Printer (PC / printer not included)		✓	✓
Computer Controlled Operation (PC software not included)			✓
Real-time Clock		✓	✓
Calibration Reminders		✓	✓
5 Year Limited Warranty	✓	✓	✓
	\$835	\$1,045	\$2,095



Micro Audiometrics Corporation
 1901 Mason Ave, Suite 104
 Daytona Beach, FL 32117
 USA

Phone: (866) 327-7226
 (386) 888-7878
 sales@microaud.com
www.microaud.com